




Product Features

- Certified to EN 1433 Load Class C - 56,000 lbs - 739 psi
- Supplied with ½ -13 x 1¾" socket head bolts to lock down grate
- Manufactured from 0.236" (6mm) thick stainless steel bars
- Suitable for use for F800 catch basin



Specifications

General

The surface drainage system shall be ACO Drain F880 catch basin complete with F880 stainless steel bar grate with bolt locking as manufactured by ACO, Inc. or similar approved.

Materials

The covers shall be manufactured from stainless steel and have **minimum** properties as follows:

- **Independently certified to meet Load Class C to EN 1433 - 56,000 lbs - 739 psi**
- **Intake area of 456 sq. in. (2941.9 cm²) per grate**

The overall width of 26.75" (680mm) and overall length of 24" (610mm). Slots measure 3.6" (91mm) by 1.0" (25mm).


Installation

The trench drain or catch basin system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

* delete as appropriate


ACO DRAIN

F880 Stainless steel bar grate




ACO Specification Information

Plan view



Side elevation



Description	Part No.	Length inches (mm)	Width inches (mm)	Weight lbs.
F880 Stainless steel bar grate	97455	24.00 (610)	26.75 (680)	63.8
Replacement Stainless steel socket head bolts (Qty 4)	93897	-	-	0.4

ACO, Inc
Northeast Sales Office
 9470 Pinecone Drive Mentor,
 OH 44060
 Tel: (440) 639-7230
 Toll free: (800) 543-4764 Fax:
 (440) 639-7235

West Sales Office
 825 W. Beechcraft St.
 Casa Grande, AZ 85122
 Tel: (520) 421-9988
 Toll Free: (888) 490-9552
 Fax: (520) 421-9899

Southeast Sales Office
 4211 Pleasant Road
 Fort Mill, SC 29708
 Toll free: (800) 543-4764
 Fax: (803) 802-1063



Electronic Contact:
 info@ACODrain.us
 www.ACODrain.us



© April 2018, ACO, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO, Inc. reserves the right to change the product and specifications without notice.

April 2018

www.ACODrain.us